

# 广东惠云钛业股份有限公司

Guangdong Huiyun Titanium Industry Corporation Limited



Technical Data Sheet

R-2021

Coated with silicon & aluminum and special organic coatings, this product is a universal purposes with high weatherability, high dispersibility, high opacity and good stability, suitable for use in coatings, plastics, paper and many other applications.

## Applications

※ Paint(water based) ※ Paint(solvent based) ※ Powder coating ※ Plastics ※ Printing ink

## Typical Properties

Parameters	Properties(typical)
TiO <sub>2</sub> Content	≥93 %
Rutile Content	≥98 %
Whiteness	Not less than the standard samples
Tinting Strength(TCS)	>1850
Volatile at 105°C	≤0.5 %
Resistivity	>80 Ω·m
Oil Absorption	≤20 g/100g
Particle Size	0.28~0.32 μm
Inorganic Coating	Silicon & Aluminium
Organic Treatment	Present

**For more data, please send e-mails to [hyamy@gdtitanium.com](mailto:hyamy@gdtitanium.com)**

Factory Add:

Fuxing Road, Liudu Town, Yun'an District Yunfu City, Guangdong Province, China

Subsidiary & Sales Office Add:

Rm2701, International Finance Edifice, 660 Central Huangpu Avenue, Tianhe District, Guangzhou, China

※The data included in the typical properties is not a specification. The information in this data sheet is a general guide to the properties of the product described in it. Nothing in this data sheet is to be construed as a warranty, express or otherwise. In all cases, it is the responsibility of the user to determine the applicability of the information and recommendations and the suitability of the products described for its own particular purpose.

※yby and any associated logos are trademarks or copyrights of GUANGDONG HUIYUN TITANIUM INDUSTRY CORPORATION LIMITED