# **1. PRODUCT AND COMPANY IDENTIFICATION**

## **1.1 Product identifiers**

Product name :Ethanol CAS-No. : 64-17-5

**1.2** Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

## 1.3 Details of the supplier of the safety data sheet

Company : Shangdong Fulaichun Group

Address: : No.188, Guzheng Zhong Road, Ruixian, Shangdong Province, China

Telephone : +86 0633-677777 Fax : +86 0633-6888889

**1.4 Emergency telephone number** Emergency Phone # : +86 0633-6777777

# 2. HAZARDS IDENTIFICATION

# 2.1 Classification of the substance or mixture GHS Classification in accordance with 29 CFR 1910 (OSHA HCS) Flammable liquids (Category 2), H225 Eye irritation (Category 2A), H319 For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word Danger

Hazard statement(s)

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

Precautionary statement(s)

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ eye protection/ face protection.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

P403 + P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS – none

# **3. COMPOSITION/INFORMATION ON INGREDIENTS**

## 3.1 Substances

Synonyms : Absolute alcohol Formula : C 2 H 6 O Molecular weight : 46.07 g/mol CAS-No. : 64-17-5 EC-No. : 200-578-6 Compositon of Ethanol

Ingerdients	Percentage	CAS No.
Ethanol	95%	64-17-5
Water	5%	7732-18-5

For the full text of the H-Statements mentioned in this Section, see Section 16.

# **4. FIRST AID MEASURES**

## 4.1 Description of first aid measures

#### **General advice**

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

### In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

### In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

#### If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

Rinse mouth with water. Consult a physician.

- **4.2 Most important symptoms and effects, both acute and delayed** The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11
- **4.3 Indication of any immediate medical attention and special treatment needed** No data available

## **5. FIREFIGHTING MEASURES**

### 5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

### 5.2 Special hazards arising from the substance or mixture

No data available

### 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

#### 5.4 Further information

Use water spray to cool unopened containers.

# 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

#### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

#### 6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in

container for disposal according to local regulations (see section 13).

### 6.4 Reference to other sections

For disposal see section 13.

# 7. HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take

measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened

must be carefully resealedand kept upright to prevent leakage.

Hygroscopic.

Storage class (TRGS 510): 3: Flammable liquids

## 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1 Control parameters

Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
Ethanol	64-17-5	TWA	1,000 ppm 1,900 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
		TWA	1,000 ppm 1,900 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
	Remarks	The value in mg/m3 is approximate.		
		STEL	1,000 ppm	USA. ACGIH Threshold Limit Values (TLV)
		Upper Respiratory Tract irritation Confirmed animal carcinogen with unknown relevance to humans		
		TWA	1,000 ppm 1,900 mg/m3	USA. NIOSH Recommended Exposure Limits
		PEL	1,000 ppm 1,900 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

# 8.2 Exposure controls

### Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

### Personal protective equipment

## Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

## Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: butyl-rubber Minimum layer thickness: 0.3 mm Break through time: 480 min Material tested:Butoject® (KCL 897 / Aldrich Z677647, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.2 mm

Break through time: 38 min

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

### **Body Protection**

Impervious clothing, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi- purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

1 0	1 1			
a) Appearance Form:	liquid, clear			
Colour:	colourless			
b) Odour	No data available			
c) Odour Threshold	No data available			
d) pH	No data available			
e) Melting point/freezing point	-143.99 °C (-227.18 °F)			
f) Initial boiling point and				
boiling range				
78.0 - 80.0 °C (172.4 - 176.0 °F)				
g) Flash point 14.0 $\%$ (57.2 $\%$ ) - closed cup				
h) Evaporation rate No data available				
i) Flammability (solid, gas) No data available				
j) Upper/lower				
flammability or				
explosive limits				
Upper explosion limit: 19 %(V)				
Lower explosion limit: 3.3 %(V)				
k) Vapour pressure 59.5 hPa (44.6 mmHg) at 20.0 °C (68.0 °F)				
l) Vapour density No data available				
m) Relative density $0.7974 \text{ g/cm}3$				

n) Water solubility completely soluble
o) Partition coefficient: n-octanol/water
log Pow: -0.349 at 24 °C (75 °F)
p) Auto-ignition
temperature
363.0 °C (685.4 °F)
q) Decomposition
temperature
No data available
r) Viscosity No data available
s) Explosive properties No data available

t) Oxidizing properties No data available

### 9.2 Other safety information

No data available

# **10. STABILITY AND REACTIVITY**

#### 10.1 Reactivity

No data available

### 10.2 Chemical stability

Stable under recommended storage conditions.

- **10.3 Possibility of hazardous reactions** Vapours may form explosive mixture with air.
- **10.4** Conditions to avoid Heat, flames and sparks.

## **10.5 Incompatible materials** Alkali metals, Oxidizing agents, Peroxides

#### 10.6 Hazardous decomposition products

Other decomposition products - No data available Hazardous decomposition products formed under fire conditions. - Carbon oxides In the event of fire: see section 5

# **11. TOXICOLOGICAL INFORMATION**

### 11.1 Information on toxicological effects

Acute toxicity LD50 Oral - Rat - male and female - 10,470 mg/kg (OECD Test Guideline 401) LC50 Inhalation - Rat - male and female - 4 h - 124.7 mg/l (OECD Test Guideline 403) LC50 Inhalation - Rat - 4 h - 30,000 mg/l No data available Skin corrosion/irritation Skin - Rabbit Result: No skin irritation (OECD Test Guideline 404)

### Serious eye damage/eye irritation

Eyes - Rabbit

Result: Causes serious eye irritation.

(OECD Test Guideline 405)

#### Respiratory or skin sensitisation

Sensitisation test:

Result: negative

Remarks: (IUCLID)

#### Germ cell mutagenicity

Ames test

Salmonella typhimurium

Result: negative

In vitro mammalian cell gene mutation test

Mouse lymphoma test

Result: negative

**OECD** Test Guideline 478

Mouse - male

### Carcinogenicity

Carcinogenicity - Mouse - Oral

Tumorigenic:Equivocal tumorigenic agent by RTECS criteria. Liver:Tumors.

Blood:Lymphomas including Hodgkin's disease.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's

list of regulated carcinogens.

### **Reproductive toxicity**

Reproductive toxicity - Human - female - Oral

Effects on Newborn: Apgar score (human only). Effects on Newborn: Other neonatal measures or effects. Effects on

Newborn: Drug dependence.

Specific target organ toxicity - single exposure

Specific target organ toxicity - repeated exposure

### Aspiration hazard

No data available

### **Additional Information**

RTECS: KQ6300000

irritant effects, respiratory paralysis, Dizziness, narcosis, inebriation, euphoria, Nausea,

Vomiting

Stomach - Irregularities - Based on Human Evidence Stomach - Irregularities - Based on Human Evidence

# **12. ECOLOGICAL INFORMATION**

## 12.1 Toxicity

Toxicity to fish flow-through test LC50 - Pimephales promelas (fathead minnow) - 15.3 mg/l -Toxicity to daphnia and other aquatic invertebrates LC50 - Ceriodaphnia dubia (water flea) - 5,012 mg/l - 48 h NOEC - Daphnia magna (Water flea) - 9.6 mg/l - 9 d Toxicity to algae EC50 - Chlorella vulgaris (Fresh water algae) - 275 mg/l - 72 h (OECD Test Guideline 201)

## 12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 15 d

Result: 95 % - Readily biodegradable.

(OECD Test Guideline 301E)

### 12.3 Bioaccumulative potential

Due to the distribution coefficient n-octanol/water, accumulation in organisms is not expected.

#### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

No data available

# **13. DISPOSAL CONSIDERATIONS**

### 13.1 Waste treatment methods

### Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

**Contaminated packaging** 

Dispose of as unused product.

# **14. TRANSPORT INFORMATION**

### DOT (US)

UN number: 1170 Class: 3 Packing group: II Proper shipping name: Ethanol Reportable Quantity (RQ): Poison Inhalation Hazard: No IMDG UN number: 1170 Class: 3 Packing group: II EMS-No: F-E, S-D Proper shipping name: ETHANOL IATA UN number: 1170 Class: 3 Packing group: II Proper shipping name: Ethanol

# **15. REGULATORY INFORMATION**

## SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

## SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

## SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

## Massachusetts Right To Know Components

	CAS-No.	<b>Revision Date</b>
Ethanol	64-17-5	1993-04-24
	<b>a</b>	

## Pennsylvania Right To Know Components

CAS-No. Revision Date

Ethanol 64-17-5 1993-04-24

New Jersey Right To Know Components

CAS-No. Revision Date Ethanol 64-17-5 1993-04-24

## California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

# **16. OTHER INFORMATION**

Full text of H-Statements referred to under sections 2 and 3.
Eye Irrit. Eye irritation
Flam. Liq. Flammable liquids
H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
Further information
Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.
The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a

guide. The information in this document is based on the present state of our knowledge and is applicable to the

product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the

product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling

or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing

slip for additional terms and conditions of sale.

## **Preparation Information**

Version: 4.14 Revision Date: 06/17/2018 Print Date: 11/10/2018